

CD12M/0B-050A1

connectors




Micro Detectors

Italian Sensors Technology



Indicative image



Electrical data

Nominal current	Max. 4 A
Wires	4
Rated impulse voltage	2,5 kV
Nominal voltage	Max. 250 V ac/dc

Mechanical data

Connections	Pin 1: brown Pin 2: white Pin 3: blue Pin 4: black
Tightening torque	0,6 Nm
Operating temperature	Plug : -25°C ... +85°C Fixed installation : -30°C ... +80°C Flexible installation: -5°C ... +80°C
1	5
Plug	M12
Outer diameter	Ø 5 mm ± 5%
Head type	Axial
Gasket material	PVC (CFC, cadmium, silicon, lead free) Flame retardant according to UL1581VW1/CSA FT1, self-extinguishing
Wire isolation	PVC (CFC, cadmium, silicon, lead free)
Bending radius	Wire for fixed installation: 5 x d Wire for flexible installation: 10 x d
Conductors section	0,34 mm ² (19 x 0,15 mm ²)

ELECTRICAL DIAGRAMS OF THE CONNECTIONS

BN/1

WH/2

BU/3

BK/4

M.D. Micro Detectors S.p.A.

Strada S. Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@microdetectors.com

date of printing

23/07/2019 15:07:07