



| Model | Code | Some possible configurations | Cut-out [mm] | Pcs /pack |
|--------|------------|------------------------------|-----------------|---------------------|
| DES 24 | 1731010024 | | 108 x 39 | 10 |

| Upon request: | 1731991020 | Set of 4 mounting screws in AISI304 with Black Dacromet finishing | 10 |
|------------------|------------|--|----|
|------------------|------------|--|----|

Splittable frame for cables with and without connectors

- ► Multiple configurations in the same frame
- ► Frame screws in AISI304 Stainless Steel
- ► Integrated gasket
- ► Strain relief according to EN 62444
- ► Sturdy construction IK10
- ▶ IP66 and Nema 4X certified







The DES 24 cable entry system consists of a splittable frame designed to accommodate small (SPP), multiple (X) or large (SPG) inserts for cables in the same frame. The inserts can be freely positioned into the frame.

Thanks to the robust construction, the DES 24 is a long lasting product.

Technical data

Material: PP+GF

Flammability: self-extinguishing acc. to

UL94-V0

Temperature: -40°C... +155°C (static) **Features:** halogens and silicones free

Related products



Inserts SPG and SPG M

Inserts SPP, SPP K, SPP M, SPP F

• •

Inserts SPP 2x
Inserts SPP 4x

. .

Flap frame

Hydraulic punch driver HY360













Ф

0

















Dimensions [mm]

