

Model	Code	Ø Cable [mm]	Model	Code	Pcs /pack
SPG 0G	1731022000	„blind“	SPG 0B	1731022020	
SPG K0G	1731022300	„blind“ pierceable Ø max. 32	SPG K0B	1731022400	
SPG 17G	1731022117	17-18	SPG 17B	1731022217	10
SPG 18G	1731022118	18-19	SPG 18B	1731022218	
SPG 19G	1731022119	19-20	SPG 19B	1731022219	
SPG 20G	1731022120	20-21	SPG 20B	1731022220	
SPG 21G	1731022121	21-22	SPG 21B	1731022221	
SPG 22G	1731022122	22-23	SPG 22B	1731022222	
SPG 23G	1731022123	23-24	SPG 23B	1731022223	
SPG 24G	1731022124	24-25	SPG 24B	1731022224	
SPG 25G	1731022125	25-26	SPG 25B	1731022225	
SPG 26G	1731022126	26-27	SPG 26B	1731022226	
SPG 27G	1731022127	27-28	SPG 27B	1731022227	
SPG 28G	1731022128	28-29	SPG 28B	1731022228	
SPG 29G	1731022129	29-30	SPG 29B	1731022229	
SPG 30G	1731022130	30-31	SPG 30B	1731022230	
SPG 31G	1731022131	31-32	SPG 31B	1731022231	
SPG 32G	1731022132	32-33	SPG32B	1731022232	
SPG 33G	1731022133	33-34	SPG33B	1731022233	
SPG 34G	1731022134	34-35	SPG34B	1731022234	

DES insert - large

- ▶ SPG: inserts for **pre-terminated cables** from 17 to 35 mm diameter
- ▶ SPG K0: blind (pierceable) version
- ▶ 2 blind version available
- ▶ Specially designed for corrugated tubes
- ▶ UL94V0 for both colours, grey and black



SPG K0



The SPG inserts enable several cables and corrugated tubes from 17 to 35 mm diameter to be installed in the DES splittable frames.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0 (grey or black)

Temperature: -40°C... +110°C (static)

Features: halogens and silicones free

Related products

- DES 24 DES Q
- DES 24-90 DESPRED 63
- DES 16 DESPRED 90
- DES 10 DESCLICK 50

